

**DAB Submersible borehole
pump stainless steel 304 1 1/4"
female thread 10,8A 230VAC
with 40m cable and control box
booster type S4 KIT 4/19 oil
cooling (7030918)**



TECHNICAL SPECIFICATIONS

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 technopolymer

Connection female thread

Type oil cooling

Voltage 230VAC

Max. temperature 40 °C

Outer ø 99 mm

Minimum medium temperature 0 °C
(continuous)

Maximum ambient temperature -10 °C

Minimum ambient temperature 40 °C

IP value IP68, class F

Type S4 KIT 4/19

Output Power 2 HP

Model with 40m cable and control box booster

Size 1 1/4"



Weight	17.5 kg
Power	1.5 kW
Impellers	19
MWC	131
Ampere	10,8 A
Max flow rate	5.4 m ³ /h
Press	1 "
BEP Capacity	3.85
BEP Head	84
PORlh	105
PORhh	64.5
PORlq	2.7
PORhq	4.6
Efficiency	61,6 %
Packaging dimensions L/W/H	120 x 120 x 1148 mm

DIMENSIONS

Db	99 mm
H-1	1094 mm

ØDi-1

1 1/4 "



PRODUCT INFORMATION

Submersible borehole pump kit with pump body and motor, power supply cable, cord and control box.

Pump maximum diameter: 99 mm

Maximum amount of sand: 150 g/m³

Installation: Fixed in vertical position or horizontal installation with a cooling sleeve.

Motor: 4OL oil-filled two-pole asynchronous DAB motor

Last modified date: 24/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>