NaanDan Button dripper plastic push-in x taper F 4ltr/h black/green type Click Tif, PC (7026016)



NaanDan by Rivulis



TECHNICAL SPECIFICATIONS

| Туре | Click Tif, PC |
|------------------|-------------------|
| Material | plastic |
| Connection | push-in x taper F |
| Opening pressure | 0,8 - 0,3 bar |
| Rec. press. | 1 - 4 bar |
| Colour | black/green |
| Flow | 4 ltr/h |

PRODUCT INFORMATION

Click Tif PC (Pressure Compensated) on-line button dripper.

Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar.

Minimum pressure at lateral end: 0.5 bar; Lateral Length exceeding 800m is not recommended.

Recommended filtration: 130 micron.

For fitting into PE40 pipe, punch 3mm hole.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal dripper for crops in uneven terrains where pressure differences are too big and using the CNL type is not possible due to its opening/closing pressure range. The PC type will open at lower pressure and keep open at higher pressures.

Last modified date: 07/11/2025

Bosta UK Ltd. Reflection House Olding Road



Bury St. Edmunds Suffolk IP33 3TA T +44 (0) 1284 716580 E enquiries@bosta.co.uk http://www.bosta.com

