

**Profec Solenoid valve
fibreglass reinforced nylon
3/4" female thread 10bar
24VDC black type 2-way NC
(7030843)**



TECHNICAL SPECIFICATIONS

Colour	black
--------	-------

Type	2-way NC
------	----------

Material	fibreglass reinforced nylon
----------	-----------------------------

Material valve	reinforced nylon
----------------	------------------

Indirect effect	yes
-----------------	-----

Material housing	reinforced nylon
------------------	------------------

Material seal	NBR
---------------	-----

Connection	female thread
------------	---------------

Right-angled model	no
--------------------	----

Minimum medium temperature 5 °C
(continuous)

Maximum ambient temperature	50 °C
-----------------------------	-------

Minimum inlet pressure	0.3 bar
------------------------	---------

Pressure	10 bar
----------	--------

Max. temp.	50 °C
------------	-------

Capacity	150 l/min
----------	-----------

Size	3/4"
------	------

Voltage

24VDC

PRODUCT INFORMATION

Standard with flow control and manual operation.

Last modified date: 23/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>