

**Profec Ball valve single union
PVC-U 25 mm glue socket
16bar DN20 grey type Safe 525
(0112141)**



TECHNICAL SPECIFICATIONS

Colour	grey
--------	------

Type	Safe 525
------	----------

Material	PVC-U
----------	-------

Operation	lever
-----------	-------

Colour lever	red
--------------	-----

Handle material	PVC-U
-----------------	-------

Housing construction	2-part
----------------------	--------

Material housing	PVC-U
------------------	-------

Material seal	hytrel/EPDM
---------------	-------------

Connection	glue socket
------------	-------------

Max. temperature	60 °C
------------------	-------

Minimum medium temperature 0 °C
(continuous)

Pressure	16 bar
----------	--------

Size	25 mm
------	-------

DN	20
----	----

DIMENSIONS

Ct-1 71 mm


Lb 100 mm

R 54 mm

ØDf 25 mm

ØDi-1 25 mm

ØDi-2 25 mm



PRODUCT INFORMATION

With secure ball.

Last modified date: 20/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>