DAB Submersible pump stainless steel 304 2" female thread 4,2A 230VAC stainless steel type Feka VS 550 M-A with float switch (7030949)

DAB WATER•TECHNOLOGY

bosta bringing water to life

TECHNICAL SPECIFICATIONS

Colour	stainless steel
Material	stainless steel 304
Pump body	stainless steel 304
Material impeller 1	stainless steel 304
Connection	female thread
Max. temperature	50 °C
Minimum medium temperature (continuous)	0 °C
Press	2 "
Maximum ambient temperature	40 °C
Minimum ambient temperature	0 °C
Type	Feka VS 550 M-A
Output Power	0,75 HP
Size	2"
Float	included
Voltage	230VAC
Power	0.55 kW

MWC	7,4
Ampere	4,2 A
Max flow rate	18 m^3/h
BEP Capacity	13.4
BEP Head	3.81
PORlh	5.19
PORhh	2.67
PORlq	9.38
PORhq	16.08

DIMENSIONS

W-1	203 mm
Cb-1	98 mm
L	492 mm
ØDi-1	2 "
Db	170 mm
H	172 mm





bosta
bringing water to life

PRODUCT INFORMATION

Power cable: 10 metre H07RN-F, with plug for the single-phase version.
Installation: fixed or portable, vertical position.
Maximum immersion depth: 7 metre
Suitable for residential waste water as sewage containing solid matter with size up to 50 mm.

Last modified date: 08/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

bosta
bringing water to life