

NaanDan Drip irrigation hose
PE 16 mm x 1,0 mm 39mil 4bar
130micron 0,5ltr/h 20cm black
500m type Amnon PC CNL
(7024185)



NaanDan
by Rivulis

TECHNICAL SPECIFICATIONS

Colour	black
Type	Amnon PC CNL
Material	PE
Filtration	130 micron
Filtration	120 mesh
Flow	0,5 ltr/h
Opening pressure	1 bar
Pressure	4 bar
Rec. press.	1 - 4 bar
Size	16 mm
Length	500 m
Inner ø	14 mm
Max. Length	180 m
Dripper spacing	20 cm
Wall thickness	39 mil
Wall thickness	1,0 mm

PRODUCT INFORMATION

The Amnon CNL (Compensated Non-Leakage) flat dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 1.0 bar.

Closing Pressure: 0.2 bar.

Pressure Regulating Range: 1.0 - 4.0 bar.

Recommended filtration: 130 micron.

Maximum Lateral Length at 0% slope.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in bags with soilless media such as strawberries.

Last modified date: 23/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>