

Hunter Pop-up sprinkler plastic
3/4" female thread 1,4 - 7bar
50°-360° black type I-20-04
(7026277)



Hunter®

TECHNICAL SPECIFICATIONS

Colour	black
Type	I-20-04
Material	plastic
Capacity	0,07 - 3,23 m ³ /h
Capacity	1,2 - 53,8 l/min
Connection	female thread
Sector adj. range	50°-360°
Angle	13 - 25 °
Max diameter	28 m
Radius	4,9 - 14 m
Pressure	1,4 - 7 bar
Rec. press.	1.7 - 4.5 bar
Size	3/4"
Riser height	10 cm

PRODUCT INFORMATION

Outstanding quality: the Hunter I-20 The Hunter I-20 is the PGP sprinkler's sturdy little brother, so it's very popular. It has an improved automatic arc return feature and a vandal-resistant motor mechanism to save you money on repairs and guaranteeing you a reliable sprinkler. An outstanding rotor in its class. The I-20 comes standard with: - 34 nozzles; - and 6 body options. Irrigation is easier with the I-20. Its flat top makes the sprinkler quick and easy to place. The radius can be altered without a problem with a Hunter wrench or flat-blade screwdriver. And if you're looking to make your sprinkler system more sustainable: There is a stainless steel riser available for the I-20. Advantages of the I-20 - The non-detachable motor mechanism is protected against damage if it is disconnected by being turned in the opposite direction. - Partial and full circle in a single model for watering different-sized zones within the same landscape. - FloStop® shuts off the water jet from the individual sprinklers so you can replace the nozzle or carry out repairs. Specifications - An automatic arc-return feature. - An adjustable arc ranging from 50 to 360 degrees. - An antileak check valve to prevent drainage from a low elevation (up to 10 feet in height). - QuickCheck™ arc mechanism for quick arc adjustment. Try the quality of this sturdy sprinkler at first hand.

Last modified date: 23/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>