

# Ebara Submersible pump stainless steel 1 1/4" female thread 5,8A 230VAC stainless steel type Best One (0930100)



# TECHNICAL SPECIFICATIONS

|        |                 |
|--------|-----------------|
| Colour | stainless steel |
|--------|-----------------|

|      |          |
|------|----------|
| Type | Best One |
|------|----------|

|          |                 |
|----------|-----------------|
| Material | stainless steel |
|----------|-----------------|

|              |         |
|--------------|---------|
| Output Power | 0,33 HP |
|--------------|---------|

|           |                     |
|-----------|---------------------|
| Pump body | stainless steel 304 |
|-----------|---------------------|

|                     |                     |
|---------------------|---------------------|
| Material impeller 1 | stainless steel 304 |
|---------------------|---------------------|

|            |               |
|------------|---------------|
| Connection | female thread |
|------------|---------------|

|         |        |
|---------|--------|
| Voltage | 230VAC |
|---------|--------|

|                  |       |
|------------------|-------|
| Max. temperature | 50 °C |
|------------------|-------|

|       |         |
|-------|---------|
| Power | 0.25 kW |
|-------|---------|

|     |   |
|-----|---|
| MWC | 9 |
|-----|---|

|        |       |
|--------|-------|
| Ampere | 5,8 A |
|--------|-------|

|               |                        |
|---------------|------------------------|
| Max flow rate | 10.2 m <sup>3</sup> /h |
|---------------|------------------------|

|       |         |
|-------|---------|
| Press | 1 1/4 " |
|-------|---------|

|                             |       |
|-----------------------------|-------|
| Maximum ambient temperature | 40 °C |
|-----------------------------|-------|

|                             |      |
|-----------------------------|------|
| Minimum ambient temperature | 5 °C |
|-----------------------------|------|

|      |        |
|------|--------|
| Size | 1 1/4" |
|------|--------|

Float

not included

## DIMENSIONS

|     |        |
|-----|--------|
| H-1 | 273 mm |
|-----|--------|

|     |        |
|-----|--------|
| W-1 | 167 mm |
|-----|--------|

|     |        |
|-----|--------|
| H-2 | 231 mm |
|-----|--------|

## PRODUCT INFORMATION

Suitable for clean and light polluted water. With built in safety and 10 metre cable.

Maximum temperature: 50°C.

Maximum dirty pass: 10 mm, 20 mm for type Best One and Best One Vox.

**Last modified date: 11/10/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>