Solar Panel HDPE 25 mm 4,5bar black with 4 hosetail connections 25 mm type 1001 (0891811)





TECHNICAL SPECIFICATIONS

Colour	black
Туре	1001
Material	HDPE
Width	820 mm
Model	with 4 hosetail connections 25 mm
Size	25 mm
Length	1280 mm
Surface	1.05 m ²

PRODUCT INFORMATION

- Low pressure drop approx 0.003 bar at 200 l/m²/h
- Flow rate to 250 l/m²/h
- Molded in one piece homogeneous black
- Weight approx. 6 kg/m² water content 6 l/m²
- Testing pressure 4.5 bar at NT
- Working pressure up to 1.2 bar 40°C
- Efficiency up to approx. 80% power up to 0.8 kWh/m²
- Average value 0.5 to 0.6 kWh/m²
- Operation possible with existing filter pump
- Non-corroding resistant to swimming-pool water
- Pool pumped direct through absorber
- Idling-proof



- Temperature-resistant from -50 to + 115°C
- Full area through flow, frost resistant, supports human weight

Last modified date: 11/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

