

**NaanDan Dripper set plastic 4
mm x 4/7 mm push-in x barbed
2ltr/h 80cm white type Click
Tif, PC CNL (7020602)**



NaanDan
by Rivulis

TECHNICAL SPECIFICATIONS

Colour	white
Type	Click Tif, PC CNL
Material	plastic
Connection	push-in x barbed
Opening pressure	0,8 - 0,3 bar
Rec. press.	1 - 4 bar
Flow	2 ltr/h
Size	4 mm x 4/7 mm
Length	80 cm

PRODUCT INFORMATION

The ClickTif CNL (Compensated Non-Leakage) on-line button dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 0.8 bar.

Closing Pressure: 0.3 bar.

Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar.

Minimum pressure at lateral end: 0.8 bar; Lateral Length exceeding 800m is not recommended.

For fitting into PE40 pipe, punch 3mm hole.

Recommended filtration: 130 micron.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in tunnels or greenhouses such as strawberries, peppers, tomato, cucumber, raspberries, eggplants, etc.

Last modified date: 23/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>