

Break tank 3/4" x 1" male thread 230VAC type Basic (7033729)



TECHNICAL SPECIFICATIONS

Tank	55 ltr
Connection	male thread
Maximum flow	4.8 ltr/min
Voltage	230VAC
Max working pressure	4 bar
Type	Basic
Size	3/4" x 1"

PRODUCT INFORMATION

Advantages over conventional separation stations

- Constant watering at maximum pressure
- Pressure increase for irrigation systems on slopes
- Fully automatic through integrated pump control
- Amortisation by reducing the sewage fee (built-in drinking water meter) *
- No noise pollution in the building
- Retrofittable
- No intervention in the drinking water installation necessary
- Outdoor / no risk of flooding for the basement
- Quick and easy installation, even without specialist tradesman possible **
- Maximum comfort and optimal security of supply
- Lockable, to prevent unauthorised access
- For seasonal outdoor use

- Optional extension by e.g. fertiliser admixture

* - Not every water supplier recognises the built-in water meter for billing the sewage fees

** - For the standard-compliant connection via the connection accessory hose, according to DIN EN 1717 and DIN 1988 100, connection must be made with a system separator type BA which can be installed on the tap.

Last modified date: 08/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>