Honeywell Filter combination brass 1" male thread 16bar DN25 DVGW type FK-06 (7003839)



Honeywell



TECHNICAL SPECIFICATIONS

FK-06 Type Material brass Approval **DVGW** Operation handle Colour lever black Handle material plastic Ball material stainless steel Material valve brass Material housing brass Material seal NBR Connection male thread Max. temperature 40 °C Max flow rate $6 \text{ m}^3/\text{h}$ Maximum ambient temperature 55 °C Pressure 16 bar 1" Size Length 180 mm



DN	25
Diameter	61 mm
Weight	1.5 kg

DIMENSIONS

Cb-1	180 mm
Ct-1	111 mm

PRODUCT INFORMATION

FK-06 rinseable filter combinations ensure a continuous supply of filtered water. They prevent the ingress of foreign matter such as particles of rust, strands of hemp and grains of sand. The accumulation of foreign particles in the base of the filter bowl can be easily removed by reverse rinsing. The pressure reducing valve prevents overpressure damage and reduces the water consumption. The appliances correspond to DIN/DVGW requirements. The compact overall dimensions enable the filter combination to be fitted even where space is limited.

- A turn on the adjuster knob is all that is required for setting
- The setting is directly readable from the setting indicator
- Filtered water supply maintained even during rinsing
- Inlet pressure balancing fluctuating inlet pressure does not influence outlet pressure
- Filter and complete filter bowl are replaceable

Last modified date: 11/10/2025

Bosta UK Ltd. Reflection House Olding Road Bury St. Edmunds Suffolk



IP33 3TA T +44 (0) 1284 716580 E enquiries@bosta.co.uk http://www.bosta.com

