

DAB Assembled pump sump PE 5,13A 230VAC grey type PE1014 Complete (7038494)



TECHNICAL SPECIFICATIONS

| | |
|---|----------------------|
| Colour | grey |
| Type | PE1014 Complete |
| Material | PE |
| Pump body | stainless steel 304 |
| Voltage | 230VAC |
| Max. temperature | 50 °C |
| Minimum medium temperature (continuous) | 0 °C |
| MWC | 9.6 |
| Max flow rate | 24 m ³ /h |
| Maximum ambient temperature | 40 °C |
| Output Power | 1 HP |
| Power | 0.75 kW |
| Ampere | 5,13 A |

PRODUCT INFORMATION

PE pump sump fitted with 2 x Feka VS 750 MNA stainless steel submersible sewage pumps. Ideally suited for wastewater and sewage water with solids not exceeding 50mm. Fully

assembled and equipped with DSD guide system, balancing valve. - PE pump pit ø 1000 x 1400 - Flat bottom - 1x inlet socket 160 mm - 1x outlet ø 90 mm - 1x cable duct ø 75 mm - 2x Feka VS 750 MNA 230 Volt 50 Hz - 2x installation set consisting of DSD guide system with ball valve and ball check valve - 1x cable protection pipe 75 mm, 5 mtr - 1x cast iron , manhole class D (heavy traffic) - 1x concrete ledge 900*900*200 mm - 1x pump control E.box with level probe and high-water float switch Application: For pumping rainwater and/or sewage containing max 50mm solids.

Last modified date: 24/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>