

**Foras Multi-stage centrifugal
pump stainless steel 304 1"
female thread 7bar 2,7A
230/400VAC blue type P 3S-
150/7 T (0920605)**



TECHNICAL SPECIFICATIONS

| | |
|---|-----------------------|
| Colour | blue |
| Material | stainless steel 304 |
| Pump body | stainless steel 304 |
| Material impeller 1 | stainless steel 304 |
| Material seal | ceramic/graphite |
| Connection | female thread |
| Max. temperature | 110 °C |
| Minimum medium temperature (continuous) | -15 °C |
| Max flow rate | 4.8 m ³ /h |
| Press | 1 " |
| Suction | 1 " |
| BEP Capacity | 3.2 |
| Efficiency | 39 % |
| Type | P 3S-150/7 T |
| Output Power | 1,5 HP |
| Size | 1" |

| | |
|------|--------|
| Seal | type M |
|------|--------|

| | |
|---------|------------|
| Voltage | 230/400VAC |
|---------|------------|

| | |
|--------|---------|
| Weight | 15.5 kg |
|--------|---------|

| | |
|-------|--------|
| Power | 1.1 kW |
|-------|--------|

| | |
|-----------|---|
| Impellers | 7 |
|-----------|---|

| | |
|-----|------|
| MWC | 80,1 |
|-----|------|

| | |
|--------|-------|
| Ampere | 2,7 A |
|--------|-------|

| | |
|----------|----|
| BEP Head | 47 |
|----------|----|

DIMENSIONS

| | |
|------|--------|
| Cb-1 | 134 mm |
|------|--------|

| | |
|------|--------|
| Cl-1 | 199 mm |
|------|--------|

| | |
|-----|--------|
| G-1 | 140 mm |
|-----|--------|

| | |
|-----|--------|
| H-1 | 211 mm |
|-----|--------|

| | |
|-----|--------|
| H-2 | 198 mm |
|-----|--------|

| | |
|---|--------|
| L | 514 mm |
|---|--------|

| | |
|----|----------|
| Lb | 214,8 mm |
|----|----------|

| | |
|------|----------|
| Lb-2 | 128,2 mm |
|------|----------|

| | |
|-----|--------|
| W-1 | 164 mm |
|-----|--------|

W-2 201 mm

ØDi-1 1 "

ØDi-2 1 "



PRODUCT INFORMATION

Stainless steel multistage horizontal pumps. Pumping of clean non-loaded fluids in the domestic, agricultural and industrial sectors; pressurising systems; irrigation; drinking and glycol water; water treatment; food industry; heating and air conditioning; washing system.

Maximum liquid temperature: from -15 up to 110 °C

Ambient temperature: max 40 °C.

Insulation class F; protection IP 44.

Supplied without cable.

Last modified date: 22/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>