

**Grundfos Multi-stage
centrifugal pump stainless
steel 1 1/4" 1,9A 400VAC type
CRI 5-5 A CA I V HQQV
(7039731)**



GRUNDFOS 

TECHNICAL SPECIFICATIONS

Material	stainless steel
Shaft	stainless steel 316
Pump body	stainless steel 316
Material impeller 1	stainless steel 304
Voltage	400VAC
Temperature range	-20°C - 90°C
Maximum ambient temperature 40 °C	
Minimum ambient temperature 0 °C	
Type	CRI 5-5 A CA I V HQQV
Output Power	1 HP
Size	1 1/4"
Power	0.75 kW
Impellers	5
MWC	35
Ampere	1,9 A
Max flow rate	8.5 m ³ /h
Suction	1 1/4 "

Efficiency 80,7 %

Motor RPM 2770

DIMENSIONS

L 160 mm

H-1 575 mm



W-1 210 mm

ØDi-1 35 mm

ØDi-2 35 mm

Cb-1 50 mm

Cb-2 50 mm



PRODUCT INFORMATION

Grundfos CRI pumps are vertical, non-self-priming, multistage, in-line, centrifugal pumps for installation in pipe systems and mounting on a foundation, suitable for industrial applications. This design provides a more compact pump design and pipework. CR pumps are designed for a variety of applications ranging from the pumping of potable water to the pumping of chemicals. The pumps are therefore suitable for a wide range of pumping systems where the performance and material of the pump meet specific demands.

Last modified date: 19/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>