

DAB Assembled pump sump PE 5,13A 230VAC black type PE814 Complete (7038493)



TECHNICAL SPECIFICATIONS

| | |
|---|----------------------|
| Colour | black |
| Type | PE814 Complete |
| Material | PE |
| Pump body | stainless steel 304 |
| Voltage | 230VAC |
| Max. temperature | 50 °C |
| Minimum medium temperature (continuous) | 0 °C |
| MWC | 9.6 |
| Max flow rate | 24 m ³ /h |
| Maximum ambient temperature | 40 °C |
| Output Power | 1 HP |
| Power | 0.75 kW |
| Ampere | 5,13 A |

PRODUCT INFORMATION

PE pump sump fitted with Feka VS 750 MA stainless steel submersible sewage pump. Ideally suited for wastewater and sewage water with solids not exceeding 50mm. Fully assembled and

equipped with DSD guide system - PE pump pit \varnothing 800 x 1400 mm - Flat bottom - 1x inlet socket \varnothing 160 mm - 1x outlet \varnothing 63 mm - 1x cable duct \varnothing 75 mm - 1x Feka VS 750 MNA 230 Volt 50 Hz - 1x installation set consisting of DSD guide system with ball valve and ball check valve - 1x cable protection pipe 75 mm, 5 mtr - 1x cast iron manhole class D (heavy traffic) - 1x concrete ledge 900*900*200 mm - 1x pump control E.box with level probe and high-water float switch
Application: For pumping rainwater / wastewater containing max 50mm solids

Last modified date: 24/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>