Break tank 3/4" x 1" male thread 230VAC BELGAQUA type Hydrobox 500 (7025398)





TECHNICAL SPECIFICATIONS

Туре	Hydrobox 500
Approval	BELGAQUA
Connection	male thread
Voltage	230VAC
Pump	Xilent X3
Tank	500 ltr
Size	3/4" x 1"
Maximum flow	120 ltr/min
Capacity Pressure	4.5 m3/h @ 5 bar

PRODUCT INFORMATION

Large break tank suitable for floor installation Flow rate: 3.4 m3/h @ 3 bar ON/OFF system integrated with dry running protector and alarms Supplied with Xilent X3 Pump with Pressure Controller Unit can be used as a booster set for at least 1 tap(s) when the water supply pressure is insufficient Integrated with Type AB air gap with 75 mm overflow connection Material Tank: PE Xilent X3 Pump Silent operational pump with varying speed drive Self-priming option Built-in 10l tank to ensure air pressure stays unchanged. Rotating inlet and outlet connections Integrated alarms against dry run, excessive pressure build-up and overheating of pump Designed to be used for residential applications in roof tanks, break tanks, rainwater tanks etc.

Last modified date: 07/11/2025



Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

