

**NaanDan Drip irrigation hose**  
**PE 20 mm x 1,2 mm 47mil 4bar**  
**130micron 1,6ltr/h 30cm black**  
**300m type Amnon PC AS**  
**(7018985)**



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

Colour	black
Type	Amnon PC AS
Material	PE
Filtration	130 micron
Filtration	120 mesh
Flow	1,6 ltr/h
Opening pressure	0,5 bar
Pressure	4 bar
Rec. press.	0,5 - 4 bar
Size	20 mm
Length	300 m
Inner ø	17,6 mm
Max. Length	240 m
Dripper spacing	30 cm
Wall thickness	47 mil
Wall thickness	1,2 mm

# PRODUCT INFORMATION

The Amnon PC (Pressure Compensated) AS (Anti-Siphon) flat dripper reduces suction at the draining stage to prevent it from blocking.

Opening Pressure: 0.5 bar.

Pressure Regulating Range: 0.5 - 4.0 bar.

Recommended filtration: 130 micron.

Maximum Lateral Length at 0% slope.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for Subsurface Drip Irrigation (SDI) as well as for above the ground irrigation.

**Last modified date: 23/02/2026**

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>