

# DAB Deep well pump stainless steel 304 1" female thread 6,1A 230VAC with 15m cable and control box booster type Micra 100M oil cooling (7030894)



# TECHNICAL SPECIFICATIONS

Material	stainless steel 304
----------	---------------------

Pump body	stainless steel 304
-----------	---------------------

Material impeller 1	noryl GFN2
---------------------	------------

Connection	female thread
------------	---------------

Type	oil cooling
------	-------------

Voltage	230VAC
---------	--------

Max. temperature	35 °C
------------------	-------

Outer ø	74 mm
---------	-------

Minimum medium temperature 0 °C (continuous)	
---	--

Max flow rate	2.7 m <sup>3</sup> /h
---------------	-----------------------

Press	1 "
-------	-----

BEP Capacity	1.8
--------------	-----

IP value	IP68
----------	------

Type	Micra 100M
------	------------


Output Power	1 HP
--------------	------

Model	with 15m cable and control box booster
-------	--

Size	1"
Weight	13.6 kg
Power	0.75 kW
Impellers	30
MWC	90
Ampere	6,1 A
BEP Head	56
PORlh	70.1
PORhh	39.6
PORlq	1.3
PORhq	2.2

## DIMENSIONS

ØDi-1	1 "
H-1	1390 mm
Db	74 mm



# PRODUCT INFORMATION

Includes assembled 15m cable and control box booster.

Pumped liquid: clean, free of solids and abrasives, non-viscous, non-aggressive, and chemically neutral, with properties similar to water.

Maximum permitted amount of sand: 40 g/m<sup>3</sup>.

Installation: in 3" wells or larger, tanks and cisterns, vertical position. In case of horizontal installation, ensure a minimum load on the thrust assembly.

**Last modified date: 08/11/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>