

**Foras Multi-stage centrifugal
pump stainless steel 304 1"
female thread 7bar 6,4A
230VAC blue type P 3S-150/7 M
(0920604)**



TECHNICAL SPECIFICATIONS

Colour	blue
Material	stainless steel 304
Pump body	stainless steel 304
Material impeller 1	stainless steel 304
Material seal	ceramic/graphite
Connection	female thread
Max. temperature	110 °C
Minimum medium temperature (continuous)	-15 °C
Max flow rate	4.8 m ³ /h
Press	1 "
Suction	1 "
BEP Capacity	3.2
Efficiency	39 %
Type	P 3S-150/7 M
Output Power	1,5 HP
Size	1"

Seal	type M
------	--------

Voltage	230VAC
---------	--------

Weight	15.5 kg
--------	---------

Power	1.1 kW
-------	--------

Impellers	7
-----------	---

MWC	80,1
-----	------

Ampere	6,4 A
--------	-------

BEP Head	47
----------	----

DIMENSIONS

Cb-1	134 mm
------	--------

Cl-1	199 mm
------	--------

G-1	140 mm
-----	--------

H-1	211 mm
-----	--------

H-2	198 mm
-----	--------

L	514 mm
---	--------

Lb	214,8 mm
----	----------

Lb-2	128,2 mm
------	----------

W-1	164 mm
-----	--------

W-2 201 mm

ØDi-1 1 "

ØDi-2 1 "



PRODUCT INFORMATION

Stainless steel multistage horizontal pumps. Pumping of clean non-loaded fluids in the domestic, agricultural and industrial sectors; pressurising systems; irrigation; drinking and glycol water; water treatment; food industry; heating and air conditioning; washing system.

Maximum liquid temperature: from -15 up to 110 °C

Ambient temperature: max 40 °C.

Insulation class F; protection IP 44.

Supplied without cable.

Last modified date: 22/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>