

**Rain Solenoid valve fibreglass
reinforced nylon 3/4" female
thread 10bar 24VAC black type
RN150 (0862901)**



TECHNICAL SPECIFICATIONS

| | |
|-----------------------------|-----------------------------|
| Colour | black |
| Material | fibreglass reinforced nylon |
| Operation | indirect servo-operated |
| Indirect effect | yes |
| Material housing | fibre-reinforced plastic |
| Material seal | NBR |
| Connection | female thread |
| Right-angled model | no |
| Temperature range | 4°C - 70°C |
| Minimum pressure difference | 1 bar |
| Frequency | 50 Hz |
| Minimum inlet pressure | 1 bar |
| Pressure | 10 bar |
| Direct current (DC) | no |
| Type | RN150 |
| Capacity | 110 l/min |
| Size | 3/4" |

Voltage

24VAC

PRODUCT INFORMATION

The plastic electric valve is for hobby or professional use.

Technical Specification:

Temperature-resistant from 4° to 70°C.

All types with flow control and manual operation.

Last modified date: 11/10/2025

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>