

**DAB Submersible borehole
pump stainless steel 304 1"
female thread 5,1A 230VAC
with 15m cable and control box
booster type Micra 75M oil
cooling (7030893)**



TECHNICAL SPECIFICATIONS

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 noryl GFN2

Connection female thread

Type oil cooling

Voltage 230VAC

Max. temperature 35 °C

Outer ø 74 mm

Minimum medium temperature 0 °C
(continuous)

Max flow rate 2.7 m³/h

Press 1 "

BEP Capacity 1.8

IP value IP68

Type Micra 75M


Output Power 0,75 HP

Model with 15m cable and control box booster

Size	1"
Weight	10.2 kg
Power	0.55 kW
Impellers	23
MWC	68
Ampere	5,1 A
BEP Head	42
PORlh	52.9
PORhh	30.3
PORlq	1.3
PORhq	2.2

DIMENSIONS

ØDi-1	1 "
H-1	1145 mm
Db	74 mm



PRODUCT INFORMATION

Includes assembled 15m cable and control box booster.

Pumped liquid: clean, free of solids and abrasives, non-viscous, non-aggressive, and chemically neutral, with properties similar to water.

Maximum permitted amount of sand: 40 g/m3.

Installation: in 3" wells or larger, tanks and cisterns, vertical position. In case of horizontal installation, ensure a minimum load on the thrust assembly.

Last modified date: 18/02/2026

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>