

NaanDan Button dripper plastic push-in x taper F 8ltr/h green type Click Tif, PC CNL (7020610)



NaanDan
by Rivulis

TECHNICAL SPECIFICATIONS

Type	Click Tif, PC CNL
Material	plastic
Connection	push-in x taper F
Opening pressure	0,8 - 0,3 bar
Rec. press.	1 - 4 bar
Colour	green
Flow	8 ltr/h

PRODUCT INFORMATION

The ClickTif CNL (Compensated Non-Leakage) on-line button dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 0.8 bar.

Closing Pressure: 0.3 bar.

Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar.

Minimum pressure at lateral end: 0.8 bar; Lateral Length exceeding 800m is not recommended.

Recommended filtration: 130 micron.

For fitting into PE40 pipe, punch 3mm hole.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in tunnels or greenhouses such as strawberries, peppers, tomato, cucumber, raspberries, eggplants, etc. The taper connection allows you to use multi-outlet connectors with 2, 4 or 8 outlets to split the flow of the dripper.

Use stakes with flow control labyrinth is recommended.

Last modified date: 18/12/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>