

**DAB Submersible pump  
stainless steel 304 2" female  
thread 5,13A 230VAC stainless  
steel type Feka VS 750 M-NA  
(7038028)**



# TECHNICAL SPECIFICATIONS

Colour stainless steel

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 stainless steel 304

Connection female thread

Max. temperature 50 °C

Minimum medium temperature 0 °C  
(continuous)

Press 2 "

Maximum ambient temperature 40 °C

Minimum ambient temperature 0 °C

Type Feka VS 750 M-NA

Output Power 1 HP

MWC 9,6 m

Size 2"

Float not included

Voltage 230VAC

Power 0.75 kW

Ampere 5,13 A

Max flow rate 24 m<sup>3</sup>/h

BEP Capacity 16.1

BEP Head 5.13

PORlh 6.8

PORhh 3.77

PORlq 11.27

PORhq 19.32

## DIMENSIONS

Cb-1 98 mm


Db 170 mm

H 172 mm

L 492 mm

W-1 203 mm

ØDi-1 2 "



# PRODUCT INFORMATION

Power cable: 10 metre H07RN-F, with plug for the single-phase version.

Installation: fixed or portable, vertical position.

Maximum immersion depth: 7 metre

Suitable for residential waste water as sewage containing solid matter with size up to 50 mm.

**Last modified date: 09/05/2026**

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>