

Rain Bird Controller plastic 24VAC white type ILX-IVM PEU 240 stations (7028618)



RAIN BIRD

TECHNICAL SPECIFICATIONS

Colour	white
Type	ILX-IVM
Material	plastic
Voltage	24VAC
Height	364 mm
Type	PEU
Number of Stations	240

PRODUCT INFORMATION

Rain Bird's new ESP-LX-IVM 2-Wire System comes with the new Integrated Valve Module (IVM).
Flow sensor inputs: up to 5 in the LX-IVM and up to 10 in the LX-IVM Pro.

This "smart solenoid" stays in constant communication with the controller, providing efficient irrigation and advanced diagnostics.

Up to four 2-Wire paths can be connected, plus flow sensing and flow management tools. Only half the number of wire splices are needed, improving installation costs and reliability. A 2-Wire path must be surge protected and grounded every 150m or every 15 devices, whichever is smaller. The IVM-SD Line Surge Protector is used for this purpose.

Wire connectors included; Languages available: EN, ES, FR, DE, IT, PT.

Last modified date: 08/11/2025

Bosta UK Ltd.
Reflection House
Olding Road

Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>