

**DAB Submersible borehole
pump stainless steel 304 2"
female thread 10,8A 230VAC
with 15m cable and control box
booster type S4 KIT 8/9 oil
cooling (7030920)**



TECHNICAL SPECIFICATIONS

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 technopolymer

Connection female thread

Type oil cooling

Voltage 230VAC

Max. temperature 40 °C

Outer ø 99 mm

Minimum medium temperature 0 °C
(continuous)

Maximum ambient temperature -10 °C

Minimum ambient temperature 40 °C

IP value IP68, class F

Type S4 KIT 8/9

Output Power 2 HP

Model with 15m cable and control box booster

MWC 54 m


Size	2"
Weight	16.8 kg
Power	1.5 kW
Impellers	9
Ampere	10,8 A
Max flow rate	10.8 m ³ /h
Press	2 "
BEP Capacity	7.2
BEP Head	45.5
PORlh	54.6
PORhh	31.9
PORlq	8.6
PORhq	5
Efficiency	65,2 %
Packaging dimensions L/W/H	120 x 120 x 1131 mm

DIMENSIONS

Db	99 mm
H-1	1031 mm

ØDi-1

2"



PRODUCT INFORMATION

Submersible borehole pump kit with pump body and motor, power supply cable, cord and control box.

Pump maximum diameter: 99 mm

Maximum amount of sand: 150 g/m³

Installation: Fixed in vertical position or horizontal installation with a cooling sleeve.

Motor: 4OL oil-filled two-pole asynchronous DAB motor

Last modified date: 09/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>