

**DAB Submersible pump
reinforced plastic 1 1/4" male
thread 3,5A 230VAC green
type Nova UP 600 M-AE
(7030948)**





TECHNICAL SPECIFICATIONS

Colour	green
Material	reinforced plastic
Pump body	technopolymer
Material impeller 1	technopolymer
Connection	male thread
Float	integrated
Voltage	230VAC
Max. temperature	35 °C
Minimum medium temperature 0 °C (continuous)	
Press	1 1/4 "
Maximum ambient temperature 40 °C	
Minimum ambient temperature 0 °C	
Type	Nova UP 600 M-AE
Output Power	0,69 HP
Size	1 1/4"
Power	0.52 kW

MWC	9,8
Ampere	3,5 A
Max flow rate	13.5 m ³ /h
BEP Capacity	10.8
BEP Head	5.74
PORlh	7.17
PORhh	4.47
PORlq	7.56
PORhq	12.96

DIMENSIONS

Db	160 mm
H-1	111.6 mm
H-2	324 mm
W-1	206 mm
ØDi-1	1 "



bosta
bringing water to life

PRODUCT INFORMATION

Installation: vertical, fixed or portable. Max. immersion depth: 7 metres.

Pump can be used with liquids containing solid particles of up to 10 mm in size.

Suited for narrow well installation requiring automatic suction up to 2/3 mm. Filter is removable.

Dry operation of max. 1 minute.

Last modified date: 24/02/2026

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>