Waterco Commercial sand filter fibreglass 4"/110mm flange 4bar type SMDD1600 (7029512)







TECHNICAL SPECIFICATIONS

Material	fibreglass
Connection	flange
Pressure	4 bar
Max. temp.	40 °C
Туре	SMDD1600
Capacity	60 m ³ /h
Size	4"/110mm
Sand	3685 kg
Filter area	2.01 m ²
Max flow rate	80 m³/h
Max. pool vol.	300 m ³

DIMENSIONS

В	1644 mm
С	2285 mm





PRODUCT INFORMATION

Waterco commercial sand filter SMDD is an upgraded version of SMD series. Besides micron fibreglass winding technology and "Fish Tail" lateral configuration, Easy Reach Air Release System and service hatch have been implemented as well. SMDD model is available in 4 bar, 6 bar, 8 bar and 10 bar pressure ratings.

Features:

- 1,2 m bed depth
- Ultra smooth bobbin finish
- Large double yoke lid with lifting eye
- Large clear sight glass
- Large stable base
- Service hatch
- Easy reach airbleed
- Flanged connections
- Fish Tail lateral
- Optional nozzle plate
- 10 years tank warranty

Last modified date: 08/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

