

Hunter Nozzle plastic female thread 1,0 - 2,1bar 0°-360° black type 15A-HE (7040015)



Hunter®

TECHNICAL SPECIFICATIONS

Material	plastic
Connection	female thread
Sector adj. range	0°-360°
Pressure	1,0 - 2,1 bar
Rec. press.	2.1 bar
Colour	black
Type	15A-HE
Capacity	0,18 - 1,01 m ³ /h
Capacity	2,95 - 16,78 l/min
Angle	25 °
Radius	4,6 m

PRODUCT INFORMATION

Hunter Pro adjustable nozzles Adjust the nozzle of your sprinkler system to make the difference between a failed crop and a good crop, a colourful landscape and a parched landscape and regular growth in your crops and irregular growth. Hunter Pro adjustable nozzles cover every corner that needs it, in every landscape, with the accuracy of a fixed nozzle. Hunter nozzles are accurate and fully adjustable to every angle between 0 ° and 360 °. There are seven models of sprinkler cap available; the distances covered range from 4 to 17 metres. Specifications - Adjustable between 0 and 360 degrees for maximum design flexibility. - Easy-grip top for easy adjustment. - Sturdy edges with a well-defined pattern so the wind cannot get a grip on the jet. -

More consistency thanks to the large drops generated by the nozzles. Extra features - Matching precipitation rate on every nozzle from 8A to 17A, for more consistency, regardless of the nozzle used. - Colour-coded for easy identification in a field or landscape. Do yourself or your customer a favour with accurate irrigation using the Hunter Pro adjustable nozzles.

Last modified date: 09/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>