Rovatti Multi-stage centrifugal pump cast iron DN65 x DN50 DIN flange 27bar 13,1A 400VAC green type ME 10K65-32/2 (7024383)



rovatti pompe

bosta
bringing water to life

TECHNICAL SPECIFICATIONS

Colour	green
Material	cast iron
Pump body	cast iron
Material impeller 1	cast iron
Connection	DIN flange
Voltage	400VAC
Max. temperature	90 °C
Minimum medium temperature (continuous)	0 °C
Press	50
Suction	65
Type	ME 10K65-32/2
Output Power	10 HP
Max. head	71 m
Size	DN65 x DN50
Power	7.5 kW
Impellers	2

Ampere	13,1 A
Max flow rate	45 m^3/h
BEP Capacity	32
BEP Head	56
Efficiency	72.3 %

DIMENSIONS

Cb-1	275 mm
Cr-1	190 mm
G-1	330 mm
H	465 mm
L	878 mm
Lb	628 mm
Mc	280 mm
Mr	348 mm
O	14 mm
W-1	380 mm
ØDi-1	65 mm
ØDi-2	50 mm







PRODUCT INFORMATION

The ME (Europa) Horizontal type is a high efficiency pump.
The lattyflon stuffing-box packing is ideal for dirty water installation because opposite to the mechanical seal where sand can damage the seal, with the stuffing-box packing there will be no issues. The stuffing-box packing needs to be adjusted accordingly with the Twinner System (2 parts) so it is always leaking in order to keep it lubricated and cool.
The ME (Europa) Horizontal pumps can also be delivered with an optional mechanical seal for clean water, please consult with us for more information.
No counter flanges are delivered with the ME (Europa) Horizaton types, for the counter flange kits please consult with us.
The ME (Europa) Horizontal type is able to supply a wide range of pressures which allows it to be used for diverse installations of medium and high pressure in irrigation with higher capacities than the compact types.

Last modified date: 12/06/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk

http://www.bosta.com

bosta
bringing water to life