

**Rain Bird Solenoid valve
fibreglass reinforced nylon 1"
female thread 13.8bar 24VAC
black type PESB (7021686)**



RAIN BIRD

TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| Colour | black |
| Type | PESB |
| Material | fibreglass reinforced nylon |
| Operation | indirect solenoid-operated with flow control handle |
| Material housing | glass-filled nylon |
| Connection | female thread |
| Pressure | 13.8 bar |
| Max. temp. | 66 °C |
| Capacity | 150 l/min |
| Size | 1" |
| Voltage | 24VAC |
| Frequency | 50 Hz |
| Minimum inlet pressure | 1.4 bar |

PRODUCT INFORMATION

The PESB solenoid valve is tough and reliable for all applications, even dirty water applications used for ponds rivers and wells.

The PESB solenoid valve is compatible with the Rain Bird irrigation decoders, and with the PRS

pressure regulator.

The PESB solenoid valve contains a scrubber, which filters dirty water very efficiently.

Last modified date: 23/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>