

**Profec Swing check valve with  
lifting device ductile iron  
(GGG40) epoxy coating DN50  
DIN flange 16bar DN50 blue  
PN10/16 (0402634)**



# TECHNICAL SPECIFICATIONS

|                   |                      |
|-------------------|----------------------|
| Colour            | blue                 |
| Material          | ductile iron (GGG40) |
| Surface treatment | epoxy coating        |
| Material cover    | ductile iron         |
| Material housing  | ductile iron (GGG40) |
| Material seal     | NBR                  |
| Connection        | DIN flange           |
| Gasket            | NBR                  |
| Temperature range | 0°C - 80°C           |
| Pressure          | 16 bar               |
| Capacity          | 41 m <sup>3</sup> /h |
| Size              | DN50                 |
| Length            | 200 mm               |
| DN                | 50                   |
| Flange            | PN10/16              |
| Outer ø           | 165 mm               |
| PCD               | 125 mm               |

## DIMENSIONS

|   |        |
|---|--------|
| L | 200 mm |
|---|--------|

|     |        |
|-----|--------|
| PCD | 125 mm |
|-----|--------|

|      |         |
|------|---------|
| Ct-1 | 82.5 mm |
|------|---------|



**Last modified date: 14/02/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

