

(7026879)



FLOTIDE

TECHNICAL SPECIFICATIONS

Colour white

Material steel

Voltage 230VAC

Temperature range 10°C - 32°C

Frequency 50 Hz

Type P2.2/32

Capacity 220 - 450 m³/h

Length 1343 mm

Width 248 mm

Height 790 mm

Noise level 44 dB

PRODUCT INFORMATION

Flotide dehumidifier absorbs moist air in the pool house and transforms it into warm, dry air. Includes defrost function to prevent icing when temperature is below 10°C. Also includes electric heater to raise the pool hall temperature 2 degrees above the water temperature which reduces evaporation. Flotide dehumidifier works as an essential partner with heat pumps on indoor pools. Installing a dehumidifier allows users to enjoy swimming in a comfortable pool house environment without problems such as wall condensation, corrosion and water damage.

Features:

- High efficiency
- Defrost and air heating function
- Super silent running at 44dB
- Epoxy fin air exchanger is featured for excellent anti-corrosion performance
- Ultra-thin casing - only 6.5cm width
- Modern glass fronted casing with touch control panel
- Stainless Steel wall mounting included
- Humidistat included - automatic shut-off when humidity level drops below 50%
- Wi-Fi module included

Last modified date: 23/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>