

DAB Assembled pump sump PE 4,3A 230VAC black type PE412 Complete (7038491)



TECHNICAL SPECIFICATIONS

Colour	black
Type	PE412 Complete
Material	PE
Output Power	0,75 HP
Pump body	technopolymer
Material impeller 1	technopolymer
MWC	7,45 m
Voltage	230VAC
Max. temperature	35 °C
Minimum medium temperature (continuous)	0 °C
Power	0.55 kW
Ampere	4,3 A
Max flow rate	16 m ³ /h

PRODUCT INFORMATION

PE pump sump fitted with Feka 600 MA submersible sewage pump. Ideally suited for wastewater, sewage and rainwater harvesting, with solids not exceeding 25mm. Fully assembled

and fitted with: - PE pump sump ø 400 x 1200 mm - Flat bottom - 1x inlet ø 125 mm - 1x outlet ø 40 mm - 1x cable duct ø 75 mm - 1x Feka 600 MA - 1x installation set consisting of ball valve, ball check valve and 3-piece coupling - 1x cable protection pipe 75 mm, 5 mtr - 1x cast iron manhole class A (walking traffic) Maximum capacity: 16.0 m³/hour Maximum head: 7.45 mWk Free passage: 25 mm Maximum wastewater temperature : 35 degrees Celsius Application: For pumping rainwater and/or slightly polluted wastewater

Last modified date: 09/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>