Flotide Sand filter HDPE 63 mm / 2" metric/imperial glue socket 2,8bar white type MFV27 (0182220)







TECHNICAL SPECIFICATIONS


Colour	white
Material	HDPE
Connection	metric/imperial glue socket
Pressure	2,8 bar
Max. temp.	50 °C
Туре	MFV27
Capacity	18 m³/h
Size	63 mm / 2"
Diameter	675 mm
Weight	20.6 kg
Sand	185 kg
Filter area	0.36 m ²
Max flow rate	18 m³/h
Max. pool vol.	101.5 m ³

DIMENSIONS

В 26 "



В	26 " inch
Α	1133 mm
В	675 mm
С	976 mm
D	910 mm



PRODUCT INFORMATION

Made of premium grade high density polyethylene. The Flotide line offers heavy duty operation and sustains a high working temperature. Only first class virgin high density polyethylene raw materials made by Phillips Chemicals are used in the production of our filters. The unique twist lock is designed for ease of servicing and maintenance of the filter.

Compact and heavy duty



- Made of high density polyethylene
- Designed for most domestic swimming pools or spa pools
- Valve lock is designed to allow 360 degree rotation to simplify installation
- Easy-to-use bayonet-locked multi-port valve lets you select any of the valve/filter operations with a simple lever-action
- Warranty period: 2 years

Last modified date: 30/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

