

**DAB Submersible pump
reinforced plastic 1 1/4" male
thread 1,5A 230VAC green
type Nova UP 300 M-AE
(7030947)**



TECHNICAL SPECIFICATIONS

| | |
|---|--------------------|
| Colour | green |
| Material | reinforced plastic |
| Pump body | technopolymer |
| Material impeller 1 | technopolymer |
| Connection | male thread |
| Float | integrated |
| Voltage | 230VAC |
| Max. temperature | 35 °C |
| Minimum medium temperature (continuous) | 0 °C |
| Press | 1 1/4 " |
| Maximum ambient temperature | 40 °C |
| Minimum ambient temperature | 0 °C |
| Type | Nova UP 300 M-AE |
| Output Power | 0,28 HP |
| MWC | 7,6 m |
| Size | 1 1/4" |

Power 0.21 kW

Ampere 1,5 A

Max flow rate 9 m³/h

BEP Capacity 10.8

BEP Head 5.74

PORlh 7.17

PORhh 4.47

PORlq 7.56

PORhq 12.96

DIMENSIONS



Db 160 mm

H-1 75.9 mm

H-2 296.2 mm

W-1 206 mm

ØDi-1 1 "



PRODUCT INFORMATION

Installation: vertical, fixed or portable. Max. immersion depth: 7 metres.

Pump can be used with liquids containing solid particles of up to 10 mm in size.

Suited for narrow well installation requiring automatic suction up to 2/3 mm. Filter is removable.

Dry operation of max. 1 minute.

Last modified date: 08/05/2026

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>