

Flotide Heat pump Inverter
metal 63 mm 19.0-6.2A
400VAC black type PC 65/R32
(7037571)



FLOTIDE

TECHNICAL SPECIFICATIONS

Colour black

Type PC 65/R32

Material metal

Condensor titanium

Fan orientation Vertical

Voltage 400VAC

Frequency 50 Hz

Phase 3

Fan speed 500-750 Rpm

Refrigerant R32

Compressor type Rotary

Compressor brand Mitsubishi

Energy label A

Nom. vol. flow rate 20 - 27 m³/h

Size 63 mm

Weight 300 kg

Ampere 19.0-6.2 A

Noise level 61 dB

Pool volume 200 - 350 m³

Max. pool vol. 350 m³

COP at A15/W25 7.5 - 4.5

Heating cap. A15/W25 57-11 kW

Fan power 0,75 kW

Noise level 46 dB

CO2 equivalent 2,63 ton

Fans (number) 1

COP at A27/W27 16.5 - 6.1

Heating cap. A27/W27 78-15 kW

Motor Power 12.75-0.91 kW

DIMENSIONS

H 1895 mm

L 1200 mm

W 980 mm

PRODUCT INFORMATION

Flotide commercial heat pump integrates full inverter technology with powerful, advanced control logic which suits commercial occasions perfectly, while ensuring high efficiency and low cost operation.

Features:

- Full inverter technology
- Stable operation from -15°C to 43°C
- Quiet running
- Automatic heating and cooling
- Automatic defrost
- 7" LED display
- High efficiency, COP up to 25
- Soft start, no voltage peaks
- 2 year warranty for heat pump, 7 year warranty for compressor and heat exchanger
- Maximum pool volume depending on environmental conditions
- Wi-Fi & 4G ready

Last modified date: 24/02/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>