

Rain Bird Drip irrigation hose
PE 16 mm x 1,2 mm 3,8bar
125micron 2,3ltr/h 33cm
brown 100m type PC inline XFS
sub surface with check valve
(7033683)



RAIN BIRD

TECHNICAL SPECIFICATIONS

Colour	brown
--------	-------

Type	PC inline XFS sub surface
------	---------------------------

Material	PE
----------	----

Filtration	125 micron
------------	------------

Length	100 m
--------	-------

Opening pressure	1 bar
------------------	-------

Maximum ambient temperature	51,7 °C
-----------------------------	---------

Pressure	3,8 bar
----------	---------

Rec. press.	1 - 3,8 bar
-------------	-------------

Wall thickness	1,2 mm
----------------	--------

Flow	2,3 ltr/h
------	-----------

Size	16 mm
------	-------

Type	with check valve
------	------------------

Inner ø	13,6 mm
---------	---------

Max. Length	137 m
-------------	-------

Dripper spacing	33 cm
-----------------	-------

PRODUCT INFORMATION

The Rain Bird drip irrigation hose, type PC inline XFS sub surface is ideal when it comes to making low maintenance systems for grasslands, shrubs or groundcover areas.

The XFS sub surface drip hose comes with an inline dripper equipped with the copper shield technology in order to prevent root intrusion into the labyrinth.

The XFS special material gives it an additional flexibility in order to avoid kinks in the coils before and during installation.

The benefit of this is to save time and material by allowing tighter turns with less fittings and stakes.

Last modified date: 07/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>