

Profec Ultrasonic watermeter messing 3/4" buitendraad 16bar DNDN15 24VDC wit MID type Class 2 (7038788)



TECHNISCHE SPECIFICATIES

Kleur	wit
-------	-----

Type	Class 2
------	---------

Materiaal	messing
-----------	---------

Keurmerk	MID
----------	-----

Verbinding	buitendraad
------------	-------------

Lengte	165 mm
--------	--------

Min. temp.	0.1 °C
------------	--------

Spanning	24VDC
----------	-------

Breedte	90 mm
---------	-------

Werkdruk	16 bar
----------	--------

IP waarde	IP68
-----------	------

Max. temp.	50 °C
------------	-------

Capaciteit	2,5 m ³ /h
------------	-----------------------

Maat	3/4"
------	------

Q1 ISO 4064 (2005)	0.01 m ³ /u
--------------------	------------------------

Q3 ISO 4064 (2005)	2.5 m ³ /u
--------------------	-----------------------

Q4 ISO 4064 (2005)	3.125 m ³ /u
--------------------	-------------------------

MinimumReadingCapacity -99999.99999

MaximumReadingCapacity 99999.99999

DN DN15

PRODUCTINFORMATIE

Ultrasonische watermeter met een batterijlevensduur van 10 jaar, IP68, R250, T50, RS485-interface met Modbus-protocol, 9600 bps, data 8bit, met MID-goedkeuring.

Gegenereerd op datum: 24-02-2026

<http://www.bosta.com>