

NaanDan Rondsproeier kunststof 1/2" buitendraad 2,5 mm paars type 5022 SD (0630073)



NaanDan
by Rivulis

TECHNISCHE SPECIFICATIES

Type 5022 SD

Materiaal kunststof

Verbinding buitendraad

Sproeihoek 25 °

Aanb. druk 3 bar

Kleur paars

Capacity 2bar 0,36 m³/u

Capacity 3bar 0,44 m³/u

Capacity 4bar 0,51 m³/u

Maat 1/2"

Max diameter 21 m

Sproeimond 2,5 mm

Radius 2bar 9,5 m

Radius 3bar 10,5 m

Radius 4bar 10,5 m

Type 5022 SD											
2,5mm x Blind			2,5mm x 1,8mm			3,2mm x blind			3,2mm x 1,8mm		
Bar	Q	D	Bar	Q	D	Bar	Q	D	Bar	Q	D
2	0,36	19	2	0,48	19	2	0,50	20	2	0,58	20
3	0,44	20	3	0,59	20	3	0,63	22	3	0,90	22
4	0,51	21	4	0,68	21	4	0,72	23	4	1,04	23



bosta
bringing water to life

PRODUCTINFORMATIE

Snelwissel nozzles bayonet systeem. Unieke hamer met SD (super diffuser) plaat.

Gegenereerd op datum: 09-11-2025

<http://www.bosta.com>